



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
ISO	GOST	d	D	B	Dyn. C	Stat. C0	
7000 AC	46100	10	26	8	5000	2350	0.025
7001 AC	46101	12	28	8	5400	2750	0.027
7002 AC	46102	15	32	9	6100	3450	0.039
7003 AC	46103	17	35	10	6750	4150	0.051
7004 AC	46104	20	42	12	10300	6100	0.089
7005 AC	46105	25	47	12	11300	7400	0.103
7006 AC	46106	30	55	13	14500	10100	0.15
7007 AC	46107	35	62	14	17500	12600	0.207
7008 AC	46108	40	68	15	18700	14600	0.247
7009 AC	46109	45	75	16	22200	17700	0.31
7010 AC	46110	50	80	16	23600	20100	0.35
7011 AC	46111	55	90	18	31100	26300	0.47
7012 AC	46112	60	95	18	31900	28100	0.5
7013 AC	46113	65	100	18	33700	31400	0.54
7014 AC	46114	70	110	20	42700	39400	0.81
7015 AC	46115	75	115	20	43600	41700	0.86
7016 AC	46116	80	125	22	53400	50600	1.11
7017 AC	46117	85	130	22	54600	53700	1.25
7018 AC	46118	90	140	24	65200	63300	1.58
7019 AC	46119	95	145	24	66600	67100	1.67
7020 AC	46120	100	150	24	68400	70600	1.72
7021 AC	46121	105	160	26	79800	81900	2.16
7022 AC	46122	110	170	28	91900	92800	2.71
7024 AC	46124	120	180	28	96600	103000	2.94
7026 AC	46126	130	200	33	117000	125000	4.43
7028 AC	46128	140	210	33	120000	133000	4.7
7030 AC	46130	150	225	35	137000	154000	5.49
7032 AC	46132	160	240	38	155000	176000	6.67
7034 AC	46134	170	260	42	186000	214000	8.92
7036 AC	46136	180	280	46	212000	253000	11.28
7038 AC	46138	190	290	46	217000	268000	12.1
7040 AC	46140	200	310	51	244000	309000	15.59
7044 AC	46144	220	340	56	267000	353000	18.5
7048 AC	46148	240	360	56	273000	375000	19.7
7052 AC	46152	260	400	65	325000	478000	28.7
7056 AC	46156	280	420	65	332000	507000	30.4



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7200 AC	46200	10	30	9	4650	2200	0.032
7201 AC	46201	12	32	10	7450	3650	0.039
7202 AC	46202	15	35	11	8100	4250	0.048
7203 AC	46203	17	40	12	10200	5500	0.069
7204 AC	46204	20	47	14	14500	8400	0.11
7205 AC	46205	25	52	15	15300	9500	0.13
7206 AC	46206	30	62	16	21300	13700	0.217
7207 AC	46207	35	72	17	19100	13700	0.313
7208 AC	46208	40	80	18	33600	23300	0.402
7209 AC	46209	45	85	19	37700	26600	0.46
7210 AC	46210	50	90	20	39400	29400	0.51
7211 AC	46211	55	100	21	48700	37100	0.68
7212 AC	46212	60	110	22	58900	45700	1.02
7213 AC	46213	65	120	23	67300	54200	1.09
7214 AC	46214	70	125	24	69800	55600	1.18
7215 AC	46215	75	130	25	79200	65200	1.32
7216 AC	46216	80	140	26	85300	71500	1.57
7217 AC	46217	85	150	28	98600	83600	2.01
7218 AC	46218	90	160	30	113000	96700	2.47
7219 AC	46219	95	170	32	122000	103000	3.02
7220 AC	46220	100	180	34	137000	117000	3.62
7221 AC	46221	105	190	36	149000	132000	4.29
7222 AC	46222	110	200	38	162000	148000	5.03
7224 AC	46224	120	215	40	174000	166000	7.08
7226 AC	46226	130	230	40	196000	198000	8.1
7228 AC	46228	140	250	42	218000	234000	9.95
7230 AC	46230	150	270	45	248000	280000	12.46
7232 AC	46232	160	290	48	230000	263000	15.49
7234 AC	46234	170	310	52	27000	331000	19.69
7236 AC	46236	180	320	52	293000	362000	20.26
7238 AC	46238	190	340	55	303000	390000	24.31
7240 AC	46240	200	360	58	324000	423000	28.82
7244 AC	46244	220	400	65	380000	540000	33.6



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7300 AC	46300	10	35	11	9300	4300	0.054
7301 AC	46301	12	37	12	11200	5250	0.065
7302 AC	46302	15	42	13	13600	7100	0.088
7303 AC	46303	17	47	14	14900	7900	0.121
7304 AC	46304	20	52	15	17400	9400	0.156
7305 AC	46305	25	62	17	24800	14400	0.248
7306 AC	46306	30	72	19	30100	18900	0.381
7307 AC	46307	35	80	21	35400	22000	0.512
7308 AC	46308	40	90	23	43200	27400	0.733
7309 AC	46309	45	100	25	55100	37100	0.97
7310 AC	46310	50	110	27	70100	48100	1.23
7311 AC	46311	55	120	29	80900	56500	1.57
7312 AC	46312	60	130	31	92500	65600	1.696
7313 AC	46313	65	140	33	105000	75300	2.38
7314 AC	46314	70	150	36	118000	85800	2.89
7315 AC	46315	75	160	37	128000	97000	3.47
7316 AC	46316	80	170	39	139000	109000	4.13
7317 AC	46317	85	180	41	150000	122000	4.91
7318 AC	46318	90	190	43	161000	135000	5.74
7319 AC	46319	95	200	45	122000	103000	6.67
7320 AC	46320	100	215	47	184000	161000	8.1
7321 AC	46321	105	225	49	208000	193000	9.28
7322 AC	46322	110	240	50	232000	226000	10.87
7324 AC	46324	120	260	55	246000	252000	16.62
7326 AC	46326	130	280	58	301000	329000	19.9
7328 AC	46328	140	300	62	329000	374000	24.31
7330 AC	46330	150	320	65	348000	414000	28.36
7332 AC	46332	160	340	68	365000	455000	34.15
7334 AC	46334	170	360	72	389000	485000	40.36
7336 AC	46336	180	380	75	409000	534000	46.72
7338 AC	46338	190	400	78	450000	598000	53.85
7340 AC	46340	200	420	80	474000	658000	60.51
7404 AC	46404	20	72	19	35600	19100	0.395
7405 AC	46405	25	80	21	39700	23200	0.527
7406 AC	46406	30	90	23	47600	28400	0.686
7407 AC	46407	35	100	25	60400	37000	0.95
7408 AC	46408	40	110	27	69900	43500	1.23
7409 AC	46409	45	120	29	84900	53800	1.55
7410 AC	46410	50	130	31	97400	65300	1.92
7411 AC	46411	55	140	33	118000	82400	2.36
7412 AC	46412	60	150	35	129000	93600	2.85
7413 AC	46413	65	160	37	139000	104000	3.41
7414 AC	46414	70	180	42	149000	115000	4.99
7415 AC	46415	75	190	45	171000	141000	5.9
7416 AC	46416	80	200	48	193000	166000	6
7417 AC	46417	85	210	52	204000	180000	8.54
7418 AC	46418	90	225	54	216000	196000	11.4



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
ISO	GOST	d	D	B	Dyn. C	Stat. C0	
7000 B	66100	10	26	8	4650	2150	0.025
7001 B	66101	12	28	8	4950	2500	0.027
7002 B	66102	15	32	9	5550	3150	0.039
7003 B	66103	17	35	10	6100	3750	0.051
7004 B	66104	20	42	12	9350	5550	0.089
7005 B	66105	25	47	12	10200	6700	0.103
7006 B	66106	30	55	13	13100	9200	0.15
7007 B	66107	35	62	14	15800	11400	0.207
7008 B	66108	40	68	15	16800	13200	0.247
7009 B	66109	45	75	16	20000	16000	0.31
7010 B	66110	50	80	16	21200	18100	0.35
7011 B	66111	55	90	18	27900	23700	0.47
7012 B	66112	60	95	18	28600	25300	0.5
7013 B	66113	65	100	18	30100	28300	0.54
7014 B	66114	70	110	20	38300	35500	0.81
7015 B	66115	75	115	20	39100	37600	0.86
7016 B	66116	80	125	22	47800	45700	1.11
7017 B	66117	85	130	22	48800	48400	1.25
7018 B	66118	90	140	24	58400	57100	1.58
7019 B	66119	95	145	24	59600	60500	1.67
7020 B	66120	100	150	24	61200	63600	1.72
7021 B	66121	105	160	26	71400	73800	2.16
7022 B	66122	110	170	28	82300	83700	2.71
7024 B	66124	120	180	28	86400	93000	2.94
7026 B	66126	130	200	33	105000	113000	4.43
7028 B	66128	140	210	33	107000	119000	4.7
7030 B	66130	150	225	35	122000	138000	5.49
7032 B	66132	160	240	38	139000	158000	6.67
7034 B	66134	170	260	42	166000	193000	8.92
7036 B	66136	180	280	46	190000	228000	11.28
7038 B	66138	190	290	46	194000	241000	12.1
7040 B	66140	200	310	51	218000	279000	15.59
7044 B	66144	220	340	56	239000	318000	18.5
7048 B	66148	240	360	56	244000	338000	19.7
7052 B	66152	260	400	65	291000	431000	28.7
7056 B	66156	280	420	65	297000	453000	30.4
7060 B	66160	300	460	74	382000	613000	43.7
7064 B	66164	320	480	74	391000	651000	46
7068 B	66168	340	520	82	450000	777000	61.8
7072 B	66172	360	540	82	461000	824000	64.6
7076 B	66176	380	560	82	472000	870000	67.2



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7200 B	66200	10	30	9	4300	2000	0.032
7201 B	66201	12	32	10	6950	3400	0.039
7202 B	66202	15	35	11	7450	3950	0.048
7203 B	66203	17	40	12	9350	5050	0.069
7204 B	66204	20	47	14	13300	7700	0.11
7205 B	66205	25	52	15	14000	8700	0.13
7206 B	66206	30	62	16	19400	12500	0.217
7207 B	66207	35	72	17	28100	18600	0.313
7208 B	66208	40	80	18	30600	21300	0.402
7209 B	66209	45	85	19	34300	24300	0.46
7210 B	66210	50	90	20	35700	26700	0.51
7211 B	66211	55	100	21	44100	33800	0.68
7212 B	66212	60	110	22	53400	41600	1.02
7213 B	66213	65	120	23	60900	49300	1.09
7214 B	66214	70	125	24	63200	50600	1.18
7215 B	66215	75	130	25	71700	59300	1.32
7216 B	66216	80	140	26	77100	65000	1.57
7217 B	66217	85	150	28	89200	76000	2.01
7218 B	66218	90	160	30	102000	88000	2.47
7219 B	66219	95	170	32	111000	94000	3.02
7220 B	66220	100	180	34	124000	107000	3.62
7221 B	66221	105	190	36	135000	121000	4.29
7222 B	66222	110	200	38	147000	135000	5.03
7224 B	66224	120	215	40	158000	151000	7.08
7226 B	66226	130	230	40	177000	180000	8.1
7228 B	66228	140	250	42	197000	213000	9.95
7230 B	66230	150	270	45	225000	254000	12.46
7232 B	66232	160	290	48	238000	279000	15.49
7234 B	66234	170	310	52	245000	300000	19.69
7236 B	66236	180	320	52	265000	329000	20.26
7238 B	66238	190	340	55	273000	353000	24.31
7240 B	66240	200	360	58	292000	384000	28.82



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7300 B	66300	10	35	11	8950	4150	0.054
7301 B	66301	12	37	12	10800	5050	0.065
7302 B	66302	15	42	13	12800	6750	0.088
7303 B	66303	17	47	14	13800	7300	0.121
7304 B	66304	20	52	15	16200	8700	0.156
7305 B	66305	25	62	17	22900	13300	0.248
7306 B	66306	30	72	19	27600	17400	0.381
7307 B	66307	35	80	21	32500	20200	0.512
7308 B	66308	40	90	23	39700	25200	0.733
7309 B	66309	45	100	25	50600	34100	0.97
7310 B	66310	50	110	27	64400	44300	1.23
7311 B	66311	55	120	29	74300	52000	1.57
7312 B	66312	60	130	31	84900	60300	1.696
7313 B	66313	65	140	33	96100	69300	2.38
7314 B	66314	70	150	36	108000	78900	2.89
7315 B	66315	75	160	37	118000	89200	3.47
7316 B	66316	80	170	39	127000	100000	4.13
7317 B	66317	85	180	41	137000	112000	4.91
7318 B	66318	90	190	43	148000	124000	5.74
7319 B	66319	95	200	45	111000	94000	6.67
7320 B	66320	100	215	47	168000	148000	8.1
7321 B	66321	105	225	49	191000	177000	9.28
7322 B	66322	110	240	50	213000	208000	10.87
7324 B	66324	120	260	55	225000	231000	16.62
7326 B	66326	130	280	58	250000	268000	19.9
7328 B	66328	140	300	62	302000	344000	24.31
7330 B	66330	150	320	65	318000	380000	28.36
7332 B	66332	160	340	68	332000	416000	34.15
7334 B	66334	170	360	72	355000	444000	40.36
7336 B	66336	180	380	75	373000	488000	46.72
7338 B	66338	190	400	78	411000	548000	53.85
7340 B	66340	200	420	80	432000	602000	60.51
7404 B	66404	20	72	19	33500	17900	0.395
7405 B	66405	25	80	21	36900	21500	0.527
7406 B	66406	30	90	23	44200	26400	0.686
7407 B	66407	35	100	25	56200	34300	0.95
7408 B	66408	40	110	27	64900	40400	1.23
7409 B	66409	45	120	29	78900	50000	1.55
7410 B	66410	50	130	31	90200	60400	1.92
7411 B	66411	55	140	33	110000	76500	2.36
7412 B	66412	60	150	35	119000	86700	2.85
7413 B	66413	65	160	37	129000	96800	3.41
7414 B	66414	70	180	42	148000	119000	4.99
7415 B	66415	75	190	45	158000	131000	5.9
7416 B	66416	80	200	48	179000	154000	6
7417 B	66417	85	210	52	189000	167000	8.54
7418 B	66418	90	225	54	200000	182000	11.4



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7000 C	36100	10	26	8	5300	2450	0.025
7001 C	36101	12	28	8	5800	2950	0.027
7002 C	36102	15	32	9	6600	3700	0.039
7003 C	36103	17	35	10	7300	4450	0.051
7004 C	36104	20	42	12	11100	6600	0.089
7005 C	36105	25	47	12	12300	8000	0.103
7006 C	36106	30	55	13	15800	11000	0.15
7007 C	36107	35	62	14	19100	13700	0.207
7008 C	36108	40	68	15	20500	15900	0.247
7009 C	36109	45	75	16	24400	19300	0.31
7010 C	36110	50	80	16	26000	21900	0.35
7011 C	36111	55	90	18	34100	28600	0.47
7012 C	36112	60	95	18	35000	30600	0.5
7013 C	36113	65	100	18	37100	34300	0.54
7014 C	36114	70	110	20	46900	43000	0.81
7015 C	36115	75	115	20	48000	45600	0.86
7016 C	36116	80	125	22	58700	55300	1.11
7017 C	36117	85	130	22	60100	58700	1.25
7018 C	36118	90	140	24	71700	69100	1.58
7019 C	36119	95	145	24	73400	73400	1.67
7020 C	36120	100	150	24	75300	77200	1.72
7021 C	36121	105	160	26	87800	89600	2.16
7022 C	36122	110	170	28	101000	101000	2.71
7024 C	36124	120	180	28	106000	113000	2.94
7026 C	36126	130	200	33	129000	137000	4.43
7028 C	36128	140	210	33	132000	145000	4.7
7030 C	36130	150	225	35	151000	169000	5.49
7032 C	36132	160	240	38	171000	193000	6.67
7034 C	36134	170	260	42	204000	234000	8.92
7036 C	36136	180	280	46	233000	276000	11.28
7038 C	36138	190	290	46	239000	293000	12.1
7040 C	36140	200	310	51	268000	338000	15.59



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7200 C	36200	10	30	9	5000	2350	0.032
7201 C	36201	12	32	10	7900	3850	0.039
7202 C	36202	15	35	11	8650	4550	0.048
7203 C	36203	17	40	12	10900	5900	0.069
7204 C	36204	20	47	14	15500	9000	0.11
7205 C	36205	25	52	15	16600	10200	0.13
7206 C	36206	30	62	16	23000	14700	0.217
7207 C	36207	35	72	17	25600	17000	0.313
7208 C	36208	40	80	18	36400	25200	0.402
7209 C	36209	45	85	19	40800	28700	0.46
7210 C	36210	50	90	20	42800	31800	0.51
7211 C	36211	55	100	21	52900	40200	0.68
7212 C	36212	60	110	22	64000	49500	1.02
7213 C	36213	65	120	23	73100	58700	1.09
7214 C	36214	70	125	24	75900	60200	1.18
7215 C	36215	75	130	25	86100	70600	1.32
7216 C	36216	80	140	26	92800	77500	1.57
7217 C	36217	85	150	28	107000	90600	2.01
7218 C	36218	90	160	30	123000	105000	2.47
7219 C	36219	95	170	32	133000	112000	3.02
7220 C	36220	100	180	34	149000	127000	3.62
7221 C	36221	105	190	36	162000	143000	4.29
7222 C	36222	110	200	38	176000	160000	5.03
7224 C	36224	120	215	40	190000	180000	7.08
7226 C	36226	130	230	40	213000	214000	8.1
7228 C	36228	140	250	42	238000	254000	9.95
7230 C	36230	150	270	45	270000	303000	12.46
7232 C	36232	160	290	48	287000	333000	15.49
7234 C	36234	170	310	52	297000	359000	19.69
7236 C	36236	180	320	52	320000	393000	20.26
7238 C	36238	190	340	55	331000	424000	24.31
7240 C	36240	200	360	58	354000	460000	28.82
7244 C	36244	220	400	65	400000	560000	33.6



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
7300 C	36300	10	35	11	9850	4600	0.054
7301 C	36301	12	37	12	10800	4900	0.065
7302 C	36302	15	42	13	13300	6850	0.088
7303 C	36303	17	47	14	15800	8400	0.121
7304 C	36304	20	52	15	18500	9950	0.156
7305 C	36305	25	62	17	26400	15300	0.248
7306 C	36306	30	72	19	32300	20300	0.381
7307 C	36307	35	80	21	37900	23600	0.512
7308 C	36308	40	90	23	46300	29400	0.733
7309 C	36309	45	100	25	59200	39700	0.97
7310 C	36310	50	110	27	75100	51600	1.23
7311 C	36311	55	120	29	86800	60600	1.57
7312 C	36312	60	130	31	99200	70300	1.696
7313 C	36313	65	140	33	112000	80700	2.38
7314 C	36314	70	150	36	126000	91900	2.89
7315 C	36315	75	160	37	137000	104000	3.47
7316 C	36316	80	170	39	149000	117000	4.13
7317 C	36317	85	180	41	161000	130000	4.91
7318 C	36318	90	190	43	173000	145000	5.74
7319 C	36319	95	200	45	133000	112000	6.67
7320 C	36320	100	215	47	197000	173000	8.1
7321 C	36321	105	225	49	223000	207000	9.28
7322 C	36322	110	240	50	249000	242000	10.87
7324 C	36324	120	260	55	265000	271000	16.62
7326 C	36326	130	280	58	294000	314000	19.9
7328 C	36328	140	300	62	353000	401000	24.31
7330 C	36330	150	320	65	374000	445000	28.36
7332 C	36332	160	340	68	394000	490000	34.15
7334 C	36334	170	360	72	418000	521000	40.36