




Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
ISO	GOST	d	D	B	Dyn. C	Stat. C0	
1200	1200	10	30	9	5480	1200	0.034
1201	1201	12	32	10	5550	1250	0.04
1202	1202	15	35	11	7480	1750	0.049
1203	1203	17	40	12	7900	2020	0.073
1204	1204	20	47	14	9950	2650	0.116
1205	1205	25	52	15	12000	3300	0.14
1206	1206	30	62	16	15800	4700	0.22
1207	1207	35	72	17	15800	5080	0.32
1208	1208	40	80	18	19200	6400	0.415
1209	1209	45	85	19	21800	7320	0.465
1210	1210	50	90	20	22800	8080	0.531
1211	1211	55	100	21	26800	10000	0.705
1212	1212	60	110	22	30200	11500	0.9
1213	1213	65	120	23	31000	12500	1.15
1214	1214	70	125	24	34500	13500	1.24
1215	1215	75	130	25	38800	15200	1.39
1216	1216	80	140	26	39500	16800	1.7
1217	1217	85	150	28	48800	20500	2.06
1218	1218	90	160	30	56500	23200	2.59
1219	1219	95	170	32	63500	27000	3.1
1220	1220	100	180	34	67400	28400	3.7
1224	1224	120	215	42	117000	51000	6.77



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
ISO	GOST	d	D	B	Dyn. C	Stat. C0	
1300	1300	10	35	11	7220	1620	0.058
1301	1301	12	37	12	9420	2120	0.067
1302	1302	15	42	13	9500	2280	0.094
1303	1303	17	47	14	12500	3180	0.13
1304	1304	20	52	15	12500	3380	0.165
1305	1305	25	62	17	17800	5050	0.255
1306	1306	30	72	19	21500	6280	0.385
1307	1307	35	80	21	25000	7950	0.51
1308	1308	40	90	23	29500	9500	0.715
1309	1309	45	100	25	38000	12800	0.955
1310	1310	50	110	27	43200	14200	1.2
1311	1311	55	120	29	51500	18200	1.6
1312	1312	60	130	31	57200	21200	1.95
1313	1313	65	140	33	61800	22800	2.42
1314	1314	70	150	35	74500	27500	3
1315	1315	75	160	37	79000	29800	3.55
1316	1316	80	170	39	86700	31400	4.17
1317	1317	85	180	41	97800	37800	5
1318	1318	90	190	43	115000	42000	5.8
1319	1319	95	200	45	132000	50800	6.7
1320	1320	100	215	47	141000	55000	8.3
2200	1500	10	30	14	8000	1800	0.048
2201	1501	12	32	14	8400	1900	0.052
2202	1502	15	35	14	8600	2000	0.056
2203	1503	17	40	16	10400	2500	0.087
2204	1504	20	47	18	16400	4100	0.13
2205	1505	25	52	18	15200	3900	0.16
2206	1506	30	62	20	15200	4600	0.26
2207	1507	35	72	23	21800	6650	0.405
2208	1508	40	80	23	22500	7380	0.505
2209	1509	45	85	23	23200	8000	0.54
2210	1510	50	90	23	23200	8450	0.58
2211	1511	55	100	25	26800	9950	0.8
2212	1512	60	110	28	34000	12500	1.09
2213	1513	65	120	31	43500	16200	1.45
2214	1514	70	125	31	44000	17000	1.5
2215	1515	75	130	31	44200	18000	1.6
2216	1516	80	140	33	48800	20200	2.15
2217	1517	85	150	36	58200	23500	2.67
2218	1518	90	160	40	70000	28500	3.37
2220	1520	100	180	46	97200	40500	4.94



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
ISO	GOST	d	D	B	Dyn. C	Stat. C0	
2300	1600	10	35	17	10000	2100	0.08
2301	1601	12	37	17	11400	2600	0.091
2302	1602	15	42	17	11800	2800	0.108
2303	1603	17	47	19	14300	3500	0.168
2304	1604	20	52	21	17800	4750	0.21
2305	1605	25	62	24	24500	6480	0.335
2306	1606	30	72	27	31500	8680	0.5
2307	1607	35	80	31	39200	11000	0.675
2308	1608	40	90	33	44800	13200	0.925
2309	1609	45	100	36	55000	16200	1.23
2310	1610	50	110	40	64500	19800	1.63
2311	1611	55	120	43	75200	23500	2.09
2312	1612	60	130	46	86800	27500	2.6
2313	1613	65	140	48	96000	32500	3.2
2314	1614	70	150	51	110000	37500	3.92
2315	1615	75	160	55	122000	42800	4.78
2316	1616	80	170	58	128000	45500	5.65
1205 K	111205	25	52	15	12000	3300	0.14
1206 K	111206	30	62	16	15800	4700	0.22
1207 K	111207	35	72	17	15800	5080	0.32
1208 K	111208	40	80	18	19200	6400	0.415
1209 K	111209	45	85	19	21800	7320	0.465
1210 K	111210	50	90	20	22800	8080	0.531
1211 K	111211	55	100	21	26800	10000	0.705
1212 K	111212	60	110	22	30200	11500	0.9
1213 K	111213	65	120	23	31000	12500	1.15
1215 K	111215	75	130	25	38800	15200	1.39
1216 K	111216	80	140	26	39500	16800	1.7
1217 K	111217	85	150	28	48800	20500	2.06
1218 K	111218	90	160	30	56500	23200	2.59
1220 K	111220	100	180	34	67400	28400	3.7
1306 K	111306	30	72	19	21500	6280	0.385
1307 K	111307	35	80	21	25000	7950	0.51
1308 K	111308	40	90	23	29500	9500	0.715
1309 K	111309	45	100	25	38000	12800	0.955
1310 K	111310	50	110	27	43200	14200	1.2
1311 K	111311	55	120	29	51500	18200	1.6
1312 K	111312	60	130	31	57200	21200	1.95
1313 K	111313	65	140	33	61800	22800	2.42
1315 K	111315	75	160	37	79000	29800	3.55
1316 K	111316	80	170	39	86700	31400	4.17
1318 K	111318	90	190	43	115000	42000	5.8
1320 K	111320	100	215	47	141000	55000	8.3
1322 K	111322	110	240	50	161000	70000	12



Bearing No.		Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
ISO	GOST	d	D	B	Dyn. C	Stat. C0	
2204 K	111504	20	47	18	16400	4100	0.13
2205 K	111505	25	52	18	15200	3900	0.16
2206 K	111506	30	62	20	15200	4600	0.26
2207 K	111507	35	72	23	21800	6650	0.405
2208 K	111508	40	80	23	22500	7380	0.505
2209 K	111509	45	85	23	23200	8000	0.54
2210 K	111510	50	90	23	23200	8450	0.58
2304 K	111604	20	52	21	17800	4750	0.21
2305 K	111605	25	62	24	24500	6480	0.335
2306 K	111606	30	72	27	31500	8680	0.5
2307 K	111607	35	80	31	39200	11000	0.675
2308 K	111608	40	90	33	44800	13200	0.925
2309 K	111609	45	100	36	55000	16200	1.23
2310 K	111610	50	110	40	64500	19800	1.63
2311 K	111611	55	120	43	75200	23500	2.09
2312 K	111612	60	130	46	86800	27500	2.6
2201 2RS	1501	12	32	14	8400	1900	0.056
2202 2RS	1502	15	35	14	8600	2000	0.059
2203 2RS	1503	17	40	16	10400	2500	0.095
2204 2RS	1504	20	47	18	16400	4100	0.138
2205 2RS	1505	25	52	18	15200	3900	0.16
2206 2RS	1506	30	62	20	15200	4600	0.26
2207 2RS	1507	35	72	23	21800	6650	0.405
2208 2RS	1508	40	80	23	22500	7380	0.505
2209 2RS	1509	45	85	23	23200	8000	0.54
2210 2RS	1510	50	90	23	23200	8450	0.58
2211 2RS	1511	55	100	25	26800	9950	0.81
2212 2RS	1512	60	110	28	34000	12500	1.09
2213 2RS	1513	65	120	31	43500	16200	1.5
2214 2RS	1514	70	125	31	44000	17000	1.58
2215 2RS	1515	75	130	31	44200	18000	1.67
2302 2RS	1602	15	42	17	11800	2800	0.111
2303 2RS	1603	17	47	19	14300	3500	0.171
2304 2RS	1604	20	52	21	17800	4750	0.22
2305 2RS	1605	25	62	24	24500	6480	0.354
2306 2RS	1606	30	72	27	31500	8680	0.5
2307 2RS	1607	35	80	31	39200	11000	0.675
2308 2RS	1608	40	90	33	44800	13200	0.925
2309 2RS	1609	45	100	36	55000	16200	1.23
2310 2RS	1610	50	110	40	64500	19800	1.63
2311 2RS	1611	55	120	43	75200	23500	2.12
2312 2RS	1612	60	130	46	86800	27500	2.62