



山东锋迪轴承有限公司

SHANDONG FODA BEARING TRANSMISSION CO., LTD



质量铸就品牌 诚信编织未来

Cast quality brand Integrity weaving the future

Recruitment of agents from all over the country



Bearing code	YQ-001	YQ-002	YQ-003
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	YQ-004	YQ-005	YQ-006
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



轴承代号	YQ-007	YQ-008	YQ-009
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



YQ-010	YQ-011	YQ-012	YQ-013



YQ-014	YQ-015	YQ-016	YQ-017



YQ-018	YQ-019	YQ-020	YQ-021

Successful people do everything possible, and those who fail are in jeopardy.

Believing that you can do it is more important than the effort itself.



Bearing code	YQ-022	YQ-023	YQ-024
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	YQ-025	YQ-026	YQ-027
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	YQ-028	YQ-029	YQ-030
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			

Every private effort will be rewarded in multiples.



Automobile clutch release bearing and its unit

[illegible][illegible][illegible]

Make money by everyone, happiness you and me.



Bearing code	YQ-043	YQ-044	YQ-045
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	MT488TF0A	YQ-047	YQ-048
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	YQ-049	YQ-050	YQ-051
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



YQ-052	YQ-053	YQ-054	YQ-055



YQ-056	YQ-057	YQ-058	YQ-059



3151000887	3151000278	3100026531

Success is never easy, but we must redouble our efforts!

Believe in yourself, believe in partners!



1602410-E3/986809K2	N-1601317-40-07/986809K2	16VA5-02050/986911K	N-1601317-40/986911K
Φ35	Φ35	Φ35	Φ44
37.5	32.25	33	39.75
47.5	48.5	49	54.5
47.8	52	48	52
Φ62	Φ62	/	/
8.7	11.66	12.7	12.6
7500	7500	6300	6600
0.583	/	0.723	0.675
FAW Light Vehicle	Jianghuai	Dongfeng Xiaobawang	Jianghuai



N1601317-40-08/986911K	986911K-16WH-02050	16QK2C-02050/986911K	986911K3-16QF-02050
Φ44	Φ44	Φ44	Φ35
30	39.75	33	34
48	53.5	45.25	52
52	52	52	48
/	/	/	Φ62
16.7	16.7	12.6	12.7
6600	6600	6600	6300
0.594	0.638	0.72	0.738
Jianghuai	Danyang Hongyun Agricultural Vehicle	Dongfeng light truck	Dongfeng two tons of vehicles



16JN-02050/360111K	16FTZ18-02050/360111K	WT4840F2/360111K	16C-02050-C/360111K
Φ47.5	Φ47.5	Φ47.5	Φ47.7
32	40	40	42
51	55	55	57
74.9	85.5	85.5	86
/	/	/	/
12.6	17.16	17.163	17.16
6600	6100	6100	6100
1.002	1.016	1.114	1.043
Dongfeng gearbox	Dongfeng gearbox	Dongfeng	Dongfeng gearbox

Grasping science and technology means grasping the economy, and grasping innovation means grasping development.



Bearing code	16C-2050BJH/360111K	16C-02050B-DF1/360111K	16C-02050B/360111K
Unit inner diameter (do) mm	Φ47.5	Φ47.5	Φ47.7
Unit fit width (to) mm	46	46	46
Unit width (t1) mm	58	61	61
Inlay width with separation fork (H) mm	74.5	85.5	86
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	17.16	17.16	17.16
Limit speed (n) r/min	6000	6100	6100
quality (W) kg	1.017	1.261	1.098
Applicable models	Shaoguan Hongda Gear	Dongfeng 145	Medium-sized car, city bus



Bearing code	WT4861F2/360111K	16JL5A-02050B/986813	1602130-09-EA/986813
Unit inner diameter (do) mm	Φ47.5	Φ47.5	Φ47.5
Unit fit width (to) mm	60.5	46	44
Unit width (t1) mm	73.5	60	59
Inlay width with separation fork (H) mm	86	85.5	85.5
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	17.16	28.74	21.1
Limit speed (n) r/min	6100	5600	5600
quality (W) kg	1.334	1.326	1.53
Applicable models	Beijing Foreign Trade	Dongfeng gearbox	Zhejiang Wanliyang Transmission



Bearing code	WT5755F2/986813	16.6B-02050JH3/986813	WT4872F2/986813
Unit inner diameter (do) mm	Φ57	Φ47.5	Φ47.5
Unit fit width (to) mm	54.5	65	72
Unit width (t1) mm	69	74	87
Inlay width with separation fork (H) mm	85.5	74.5	85.5
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	21.1	28.74	21.1
Limit speed (n) r/min	5600	5600	5600
quality (W) kg	1.66	1.479	1.645
Applicable models	Shaoguan Hongda Gear		Dongfeng



16C-02050B2/360111K	WT4846F2/360111K	16RN3-02050B/360111K	16.6B-02050G/360111K
Φ47.7	Φ47.5	Φ47.5	Φ47.5
46	46	50	50
61	61	61	62
86	85.5	85.5	85.5
/	/	/	/
17.16	17.163	17.16	17.16
6100	6100	6100	6000
1.089	1.115	1.14	1.114
Dongfeng 140-2	Dongfeng	Medium-sized car, city bus, Dongfeng 145	Dongfeng light vehicle



WT4846F2/986813	WT4852F2/986813	WT4858F2/986813	16.6B-02050N1/986813
Φ47.5	Φ47.5	Φ47.5	Φ57
46	52	58	41
60	66	72	56
85.5	85.5	85.5	85.5
/	/	/	/
21.1	21.1	21.1	28.74
5600	5600	5600	5600
/	1.401	1.464	1.209
Dongfeng	Dongfeng	Dongfeng	Shaoguan Hongda Gear



16N-02050-996713K	1602130-660/996713K	NT5737F3/996713KH	85NT5740F2/996714
Φ57	Φ57	Φ57	Φ57
37	47	37	40
56	66	56	59
74.9	75	75	75
/	/	/	/
26.49	26.5	26.5	33.4
5600	5600	5600	5300
1.503	1.88	1.671	1.521
FAW, Dongfeng heavy truck	FAW, Dongfeng heavy truck		

Cummins engine

Small things make great things, and the details are perfect.

Good habits make a lifetime, bad habits ruin the future.



Bearing code	WT5787F2/996914	NT2617F0	NT3630F6
Unit inner diameter (do) mm	Φ57.175	Φ26	Φ35.6
Unit fit width (to) mm	86.7	17	30
Unit width (t1) mm	104	27.5	40
Inlay width with separation fork (H) mm	85.7	62.5	48
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	33.4	12.7	11.11
Limit speed (n) r/min	5600	10000	8200
quality (W) kg	2.22	0.242	0.41
Applicable models	North Ben	Rada, Russia	Steyr



Bearing code	NT4542F2	NT4842F2	81NZ4821
Unit inner diameter (do) mm	Φ45	Φ47.7	Φ47.5
Unit fit width (to) mm	41.5	41.5	59
Unit width (t1) mm	60.5	57.5	75
Inlay width with separation fork (H) mm	64.8	86	86
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	23.56	21.1	27.6
Limit speed (n) r/min	6000	6000	5600
quality (W) kg	1.03	1.37	/
Applicable models		Zhuzhou Gear	FAW 5 ton king



Bearing code	NT5742F2A	NT5745F2	NT5747F2
Unit inner diameter (do) mm	Φ57	Φ57	Φ57
Unit fit width (to) mm	42	45	47
Unit width (t1) mm	62	64	61.8
Inlay width with separation fork (H) mm	75	75	86
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	33.4	33.4	27.6
Limit speed (n) r/min	5300	4300	5600
quality (W) kg	1.653	1.77	1.64
Applicable models	FAW eight tons	Yutong Automobile	Yuchai



NT4231F3	NT4238F3	62NT4435F2	F-45535
Φ42	Φ42	Φ44	Φ44.6
31	38	34.5	36.4
46.5	49	51	52.2
56	50	54	Φ53
/	/	/	/
23.56	23.56	14.84	29.34
7500	7500	6000	7000
0.978	1.12	0.76	0.806
Mercedes	Mercedes	Xingrui gear	Ford



81NT4859F2	NT5472F3	NT5492F3	NT5740F2A
Φ47.5	Φ54	Φ54	Φ57
59	71.5	91.5	40
75	83.5	103.5	59
86	92	92	75
/	/	/	/
27.6	33.4	33.4	33.4
5600	4300	4300	5300
/	2.136	2.25	1.623
FAW 5 ton king	Mercedes	Mercedes	bus



NT5748F3	86NT5760F2	NT6650F2	WT6658F2
Φ57	Φ57	Φ66	Φ66
48	60	50	57.6
67	80	82	91.6
74.9	86	126	126
/	/	/	/
36.5	27.6	30.69	36.89
5600	5600	5600	4500
1.983	1.78	2.523	2.83
Dongfeng	FAW Liberation	Volvo	Volvo

If you can still work hard and pay, don't stop and give up.

Every time something happens, the heart will be calm, and the god will be quiet.



Bearing code	34RCTY2419F0	34RCTY2426F0	34RCTY2618F0
Unit inner diameter (do) mm	Φ24.08	Φ24	Φ26.1
Unit fit width (to) mm	18.5	26	17.5
Unit width (t1) mm	28.5	41	30
Inlay width with separation fork (H) mm	61.3	37.5	30
Contact circle diameter (D1) mm	Φ34	Φ34	Φ34
Dynamic load rating (Ca) KN	7.89	8.44	8.44
Limit speed (n) r/min	9000	9000	9000
quality (W) kg	0.11	0.12	0.075
Applicable models	Sign, Citroen	Fiat	Volkswagen



Bearing code	44RCT2802	44RCT2802A	44TKB2805
Unit inner diameter (do) mm	Φ28	Φ28	Φ28
Unit fit width (to) mm	22	22.5	22
Unit width (t1) mm	32	32.5	28
Inlay width with separation fork (H) mm	55	55	45
Contact circle diameter (D1) mm	Φ44	Φ44	Φ44
Dynamic load rating (Ca) KN	8	8	8
Limit speed (n) r/min	10000	10000	10000
quality (W) kg	0.138	0.153	0.155
Applicable models	Hafei Lubao	Changhe Suzuki, Chery QQ	Xiali, Geely



Bearing code	44RCT2822F0A	50RCTY2822F0	40RCT2826F0
Unit inner diameter (do) mm	Φ28	Φ28	Φ28.1
Unit fit width (to) mm	22	22	26
Unit width (t1) mm	32	32	44
Inlay width with separation fork (H) mm	52	55	90.4
Contact circle diameter (D1) mm	Φ44	Φ50	Φ40
Dynamic load rating (Ca) KN	7.94	8.62	11.52
Limit speed (n) r/min	10000	10000	9000
quality (W) kg	0.141	0.146	0.250
Applicable models	Changan Benben 1.0L	Antelope, Yue Xiang	Zhongtai Automobile



36RCTY2619F0	44CTY2619F0	50CTY2619F0	34RCTY2620F0
Φ25.7	Φ25.5	Φ25.5	Φ26.1
18.7	19	19	20
24	24.6	24.6	31.9
34.5	34.45	34.45	30
Φ36	crew cut	crew cut	Φ34
9.75	9.51	9.51	8.44
9000	9000	9000	9000
0.146	0.089	0.096	0.074
Volkswagen Touran	Volkswagen, Southeast V3, V5, Bora	Guangqi chuanqi	Renault



48RCT2821F0	48CT2822F0	48RCTY2822F0	44RCTY2822F0A
Φ28	Φ28	Φ28	Φ28
21	22.3	22.5	22
24	30	32.5	32
45	44.8	70	52
Φ48	crew cut	44	44
8	7.56	9.55	8.62
10000	10000	10000	10000
0.145	0.160	0.152	0.140
Wuling Hongtu	Wuling Hongguang	Changhe Suzuki	Changan Benben mini



40RCT2826F0A	47RCT3001	55RCT3022F0	47RCT3123F0
Φ28.1	Φ30	Φ30	Φ31
26	19.5	22.3	23
30	24.5	28.3	40.8
42	45	45	68
Φ40	Φ47	55	Φ47
11.52	7.56	10.18	8.25
9000	10000	9000	10000
0.237	0.132	0.248	0.188
Dongfeng Xiaokang, Zhongtai Lang Yueqian	Alto	Northern gearbox	BYD F3

There is no natural confidence, only the confidence that is constantly cultivated.

Grasping one today is better than two tomorrows.



Bearing code	48CTY3123F0	54RCTY3123F0	48TKB3201
Unit inner diameter (do) mm	Φ31.1	Φ31.1	Φ32
Unit fit width (to) mm	22.5	23	38
Unit width (t1) mm	29.5	31	50
Inlay width with separation fork (H) mm	41.5	41.6	40
Contact circle diameter (D1) mm	crew cut	Φ54	Φ48
Dynamic load rating (Ca) KN	12.73	13.3	8.45
Limit speed (n) r/min	9000	9000	9000
quality (W) kg	0.138	0.135	0.348
Applicable models	Volkswagen	FAW Pentium	Jiangling pickup, Isuzu



Bearing code	48RCT3221F0	54RCTS3221F0	55RCTY3221F0
Unit inner diameter (do) mm	Φ31.75	Φ32	Φ32
Unit fit width (to) mm	21	21	21
Unit width (t1) mm	33	33	29
Inlay width with separation fork (H) mm	60	60	60
Contact circle diameter (D1) mm	Φ48	Φ54	55
Dynamic load rating (Ca) KN	8.57	8.57	10.70
Limit speed (n) r/min	9000	9000	9000
quality (W) kg	0.22	0.197	0.163
Applicable models	Zhonghua Car, Southeast Lingshuai	BYDF6、S6	BYDF6、S6



Bearing code	55RCT3227F1	48RCT3231F0	48CT3235F0
Unit inner diameter (do) mm	Φ31.5	Φ32	Φ31.75
Unit fit width (to) mm	27	30.5	35
Unit width (t1) mm	34.5	42.5	47
Inlay width with separation fork (H) mm	46	40	46
Contact circle diameter (D1) mm	Φ55	48	平头
Dynamic load rating (Ca) KN	10.57	8.45	8.45
Limit speed (n) r/min	7500	9000	9000
quality (W) kg	0.3285	0.3	0.312
Applicable models	Mitsubishi, Hyundai	Isuzu	Ai Xin



54RCT3202	55TKB3203	55RCTY3219F0	48RCTY3221F0
Φ32	Φ32	Φ31.72	Φ31.72
32	32	18.9	21
40	40	33	35
46	46	62	62
Φ54	Φ55	Φ55	Φ48
8.45	8.45	10.7	10.7
8000	8000	8000	8000
0.292	0.297	0.133	0.132
Southeast Fulika, Cheetah	Southeast Fulika, Cheetah	Huatai Santa Fe, Tusheng, Jianghuai	Maxima, Hyundai Elantra, Jianghuai



50CT3221F0	48RCT3222F0	60RCT3225F0	60RCT3225F0A
Φ31.75	Φ31.75	Φ32	Φ32
20.5	21.9	25	25
30	30.2	41	39
46	45.35	40	40
crew cut	48	Φ60	60
8.45	8.57	12.24	11.70
9000	9000	6000	6000
0.267	0.188	0.295	0.308
Wuling wide-body bread	Ougerui, Beiqi Weiwang	Isuzu, JAC Light Truck	Isuzu, JAC Light Truck



48RCT3238F0	54CTY3238F0	55RCT3238F0	RCTS338SA
Φ31.75	Φ32	Φ32	Φ33
38	37.5	38	22.3
50	39.5	50	33.3
46	79.4	40	70.65
Φ48	平头	Φ55	Φ50
8.45	10.7	8.45	6.34
9000	8000	9000	10000
0.349	0.209	0.269	0.25
Changfeng Cheetah JCS7	Ai xin	Ai xin	Changan Star

When I am not waiting, I will try my best to make a difference and challenge my achievements.

The mountain will fall down, the water will flow, and you will never fall on your own.



Bearing code	48RCT3303	48RCT3303B	50RCT3304
Unit inner diameter (do) mm	Φ33	Φ33	Φ33
Unit fit width (to) mm	23.4	23.4	22.3
Unit width (t1) mm	28	31	33.3
Inlay width with separation fork (H) mm	42.5	42.5	70
Contact circle diameter (D1) mm	48	Φ48	50
Dynamic load rating (Ca) KN	10.25	10.18	10.25
Limit speed (n) r/min	9000	9000	9000
quality (W) kg	0.218	0.229	0.213
Applicable models	Changan Automobile	Changhe Suzuki	Feilubao



Bearing code	48RCT3222F0C	54RCTY3322F0	54CT3338F2
Unit inner diameter (do) mm	Φ33	Φ33	Φ33
Unit fit width (to) mm	22	22	37.5
Unit width (t1) mm	31	29	47.5
Inlay width with separation fork (H) mm	79.2	70	43.8
Contact circle diameter (D1) mm	Φ50	Φ50	平头
Dynamic load rating (Ca) KN	10.2	11.45	11.7
Limit speed (n) r/min	7000	9000	7200
quality (W) kg	0.22	0.218	0.64
Applicable models	Great Wall Gorgeous, Great Wall Elf Tengyi C30, Harford M2	BYDF0	Foton Light Card



Bearing code	RCT356SA9	62RCT3503	54RCT3521
Unit inner diameter (do) mm	Φ35	Φ35	Φ35
Unit fit width (to) mm	33.8	37.5	33
Unit width (t1) mm	44.5	47.5	49
Inlay width with separation fork (H) mm	44	47.8	48
Contact circle diameter (D1) mm	Φ51	Φ62	Φ54
Dynamic load rating (Ca) KN	10.57	11.7	11.7
Limit speed (n) r/min	7500	6000	6000
quality (W) kg	0.35	0.447	0.645
Applicable models	Gold cup	Red tower light truck	Southeast Delica, Jiangling Motors



Bearing code	50RCT3304A	50RCT3304C	48RCT3321F0A	50RCT3322F0
Unit inner diameter (do) mm	Φ33	Φ33	Φ33	Φ33
Unit fit width (to) mm	22.3	22.3	21.3	22
Unit width (t1) mm	33.3	33.3	29.8	31
Inlay width with separation fork (H) mm	70	70.65	50	70
Contact circle diameter (D1) mm	50	Φ50	Φ48	Φ50
Dynamic load rating (Ca) KN	10.25	12.37	10.18	8.57
Limit speed (n) r/min	9000	9000	9000	10000
quality (W) kg	0.308	0.175	0.229	0.177
Applicable models	Changan Automobile	Changan Automobile	Changan Automobile	Geely Emgrand, King Kong, Toyota Corolla



Bearing code	50CTY3414F0	48RCT3421F0	54CT3421F0	53CT3422F0A
Unit inner diameter (do) mm	Φ34	Φ34.05	Φ34.05	Φ34
Unit fit width (to) mm	14	20.5	20.5	21.5
Unit width (t1) mm	31.5	29	29	30.5
Inlay width with separation fork (H) mm	72	44.5	44.5	79.2
Contact circle diameter (D1) mm	crew cut	Φ48	crew cut	crew cut
Dynamic load rating (Ca) KN	13.28	8.5	8.45	10.7
Limit speed (n) r/min	7000	9000	9000	7000
quality (W) kg	0.225	0.26	0.261	0.253
Applicable models	Volkswagen Santana	Jiangling Motors	Jiangling Landwind	Great Wall Motor



Bearing code	60RCT3525F0	65RCT3525F0	58RCT3527F0/A	62CT3530F2
Unit inner diameter (do) mm	Φ35	Φ35	Φ35	Φ35
Unit fit width (to) mm	25	25	27	30
Unit width (t1) mm	48.5	48.5	37	46
Inlay width with separation fork (H) mm	52	52	44	48
Contact circle diameter (D1) mm	Φ60	Φ65	Φ58	Φ62
Dynamic load rating (Ca) KN	12.24	12.24	13.44	11.72
Limit speed (n) r/min	9000	9000	6600	6000
quality (W) kg	0.301	0.320	0.389	0.68
Applicable models	Jianghuai Light Card, Isuzu	Jianghuai Shuai Ling	ZTE pickup	Jiangling Light Truck

Learning to change ideas, ideas change actions, actions change fate.

Unite as one, and its profit is broken! Unite and create new achievements!



54RCT3538F2	58RCT3731F0B	55CT3741F0	55CT3741F3
Φ35	Φ37	Φ36.5	Φ36.5
37.5	31	40.5	40.5
54	51	50	50
48	56	49.5	49.5
Φ54	Φ58	crew cut	crew cut
11.7	11.86	11.72	11.72
6000	9000	6000	6000
0.701	0.351	0.69	0.69
Nanjing Iveco Light Truck	Jianghuai Ruifeng Mazda	Kawei Automobile, ZTE Pickup	Kawei Automobile, ZTE Pickup



70CT4032F0	62CT4440F2	68CT4456F2	70CT4832F0
Φ40	Φ44	Φ44	Φ48
32	40	55.5	32
51.5	55	66	51.5
52.2	53.5	55.8	60
crew cut	crew cut	crew cut	crew cut
16.09	15.42	19.2	13.82
6000	6000	6000	6000
0.64	1.67	1.1927	0.617
Isuzu	Nanjing Iveco	FAW Three Tons	Isuzu ,Jiangling ,Jianghuai



78CT4845F2	81CT4846F2A	68CT4852F2	81CT4854F2
Φ47.5	Φ47.5	Φ47.5	Φ47.5
45	46	51.5	54
64	61	66	69
74.9	86	86	86
crew cut	crew cut	crew cut	crew cut
33.4	25.5	19.2	25.5
5300	4000	6000	4000
1.901	1.486	1.33	1.66
Dongfeng Tianjiing	Jianghuai	Jianghuai cross country	Jianghuai

The current effort is not for the present reward, but for the future.



Bearing code	78CT4855F3	78CT4858F2	81CT4859F0
Unit inner diameter (do) mm	Φ47.7	Φ47.5	Φ47.5
Unit fit width (to) mm	55	58	59
Unit width (t1) mm	70	77	75
Inlay width with separation fork (H) mm	85.7	74.9	86
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	33.4	33.45	28.17
Limit speed (n) r/min	5300	5300	5600
quality (W) kg	2.15	2.085	1.796
Applicable models	Fashite	Dongfeng	FAW heavy truck



Bearing code	86CT5646F3	68RCT5656F0	68RCT5657F3
Unit inner diameter (do) mm	Φ56	Φ56	Φ56
Unit fit width (to) mm	46	56	57
Unit width (t1) mm	61	75	67
Inlay width with separation fork (H) mm	74.5	74.9	69.8
Contact circle diameter (D1) mm	crew cut	Φ68	Φ68
Dynamic load rating (Ca) KN	33.4	25.53	25.53
Limit speed (n) r/min	6300	6000	6000
quality (W) kg	1.602	1.411	1.401
Applicable models	Jianghuai heavy truck		



Bearing code	CT5740F0	CT5740F3	85CT5740F0A
Unit inner diameter (do) mm	Φ57.2	Φ57	Φ57
Unit fit width (to) mm	40	40	40
Unit width (t1) mm	59	59	55
Inlay width with separation fork (H) mm	74.9	75	85.7
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	22.42	33.4	33.4
Limit speed (n) r/min	5600	5300	5300
quality (W) kg	1.235	1.65	1.53
Applicable models	Yutong Bus, Jinlong Bus	Yutong, Jinlong, FAW	FAW

Seek truth and beauty, and stick to one's ambition



Bearing code	76CT4859F2	81CT5153F0	86CT5164F0	86CT5640F0
Unit inner diameter (do) mm	Φ47.7	Φ50.5	Φ51.4	Φ56
Unit fit width (to) mm	59	52.5	63.5	40
Unit width (t1) mm	80	81	79	50.5
Inlay width with separation fork (H) mm	85.5	68	72.7	68
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	30.13	22.42	22.42	35.7
Limit speed (n) r/min	6000	5600	5600	4600
quality (W) kg	1.95	0.827	0.779	1.4
Applicable models	Fashite	Benz	Benz	Isuzu



Bearing code	78CT5737F0	78CT5737F3	78CT5737F3B	86CT5738F6
Unit inner diameter (do) mm	Φ57	Φ57	Φ57	Φ57
Unit fit width (to) mm	37	37	37	37.5
Unit width (t1) mm	56	56	56	56
Inlay width with separation fork (H) mm	74.9	74.9	74.9	74.9
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	33.4	33.4	33.4	33.45
Limit speed (n) r/min	5300	5300	5300	5300
quality (W) kg	1.46	1.83	1.83	1.05
Applicable models	Dongfeng	Dongfeng	Dongfeng	Dongfeng



Bearing code	85CT5740F3	86CT5740F3	86CT5742F2A	86CT5744F2
Unit inner diameter (do) mm	Φ57.175	Φ57	Φ57	Φ57
Unit fit width (to) mm	40	40	42	44
Unit width (t1) mm	55	50	61	55
Inlay width with separation fork (H) mm	85.7	75	75	75
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	35.7	33.4	33.45	33.4
Limit speed (n) r/min	5300	5300	5300	5300
quality (W) kg	2.21	1.515	1.601	1.56
Applicable models	FAW	Jinan Heavy Duty Truck	FAW heavy truck	Dongfeng heavy truck

Do not tighten the quality of the strings, can not play the tone of the market.



Bearing code	86CT5746F0	CT5747F0	78CT5747F0
Unit inner diameter (do) mm	Φ57.2	Φ57	Φ57
Unit fit width (to) mm	46	47	47
Unit width (t1) mm	65	57	66
Inlay width with separation fork (H) mm	74.9	74.3	75
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	22.42	33.4	33.4
Limit speed (n) r/min	5600	5300	5300
quality (W) kg	1.275	1.639	1.682
Applicable models	Iveco, Benz	Yutong Bus, Jinlong Bus	Yutong Bus, Jinlong Bus



Bearing code	78CT5753F2	CT5755F3	78CT5759F0
Unit inner diameter (do) mm	Φ57	Φ57	Φ57
Unit fit width (to) mm	53	55	59
Unit width (t1) mm	72	65	78
Inlay width with separation fork (H) mm	74.9	74.3	74.9
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	33.4	33.4	33.4
Limit speed (n) r/min	5300	5300	5300
quality (W) kg	2.09	2.003	2.172
Applicable models	Dongfeng Tianjing, Wuhan Xiaolong	Jinlong Bus	Dongfeng heavy truck



Bearing code	85CT5765F2	CT5756F0	85CT5771F2
Unit inner diameter (do) mm	Φ57.175	Φ57	Φ57
Unit fit width (to) mm	65	56	71
Unit width (t1) mm	78	76	90
Inlay width with separation fork (H) mm	85.7	75	74.9
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	35.76	36	33.45
Limit speed (n) r/min	4600	5200	5300
quality (W) kg	2.229	3.2	2.400
Applicable models	Dongfeng heavy truck	Oumake	

Cultivate today, harvest tomorrow.



Bearing code	86CT5747F2	CT5747F3	996713KTA	CT5752F3
Unit inner diameter (do) mm	Φ57	Φ57	Φ57	Φ57
Unit fit width (to) mm	47	47	47	52
Unit width (t1) mm	66	57	57	62
Inlay width with separation fork (H) mm	75	74.3	75	74.3
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	33.45	33.4	33.4	33.4
Limit speed (n) r/min	5300	5300	5300	5300
quality (W) kg	1.808	1.650	1.750	1.928
Applicable models	Jinlong Bus	Yutong Bus, Jinlong Bus	Jinlong Bus	Jinlong Bus



Bearing code	78CT5759F2	78CT5759F2A	86CT5760F2	85CT5765F0
Unit inner diameter (do) mm	Φ57	Φ57	Φ57	Φ57.175
Unit fit width (to) mm	59	59	60	65
Unit width (t1) mm	78	78	80	78
Inlay width with separation fork (H) mm	74.9	74.9	86	85.7
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	33.4	33.45	33.45	35.76
Limit speed (n) r/min	5300	5300	5300	4600
quality (W) kg	2.172	2.100	2.123	2.360
Applicable models	Dongfeng heavy truck	Fashite	FAW heavy truck	Dongfeng heavy truck



Bearing code	78CT5775F2	85CT5787F0	85CT5787F2	86CT6042F2
Unit inner diameter (do) mm	Φ57	Φ57	Φ57	Φ60
Unit fit width (to) mm	75	86.7	86.7	42
Unit width (t1) mm	94	104	104	61
Inlay width with separation fork (H) mm	74.9	85.7	85.7	75
Contact circle diameter (D1) mm	crew cut	crew cut	crew cut	crew cut
Dynamic load rating (Ca) KN	33.45	35.70	35.70	33.45
Limit speed (n) r/min	5300	4600	4600	5300
quality (W) kg	2.336	2.612	2.612	1.596
Applicable models	Fashite	FAW heavy truck	FAW heavy truck	Electric bus

Pay and you will be rewarded!



Bearing code	36CL2716F0	43CL3327F0	44CL3642F0
Unit inner diameter (do) mm	Φ27.08	Φ33.1	Φ36
Unit fit width (to) mm	16.05	27.2	42
Unit width (t1) mm	26.05	41	58
Inlay width with separation fork (H) mm	64.45	68.7	68
Contact circle diameter (D1) mm	Φ36.3	Φ43.2	Φ44
Dynamic load rating (Ca) KN	9.90	10.25	13.4
Limit speed (n) r/min	10000	9000	9000
quality (W) kg	0.230	0.402	0.393
Applicable models	Jianghuai Heyue	Iveco, Paijero	Iveco



Bearing code	86NL5870F0	86CL5874F0	86NL5876F0
Unit inner diameter (do) mm	Φ57.5	Φ58.2	Φ58.4
Unit fit width (to) mm	70	74	75.5
Unit width (t1) mm	90	89	91.5
Inlay width with separation fork (H) mm	104	134	134
Contact circle diameter (D1) mm	Φ85.6	Φ86	Φ86
Dynamic load rating (Ca) KN	28.49	31.90	43.02
Limit speed (n) r/min	4300	4300	4300
quality (W) kg	2.059	2.490	3.100
Applicable models	Auman, Steyr, Volvo	Volvo	Volvo



Bearing code	86CL6081F2/A	70CL6082F0A	86NL6082F0A
Unit inner diameter (do) mm	Φ60	Φ60	Φ60.2
Unit fit width (to) mm	81	82	81.5
Unit width (t1) mm	100	105.5	95.5
Inlay width with separation fork (H) mm	138.5	77.9	127.9
Contact circle diameter (D1) mm	Φ85.5	Φ70	Φ86
Dynamic load rating (Ca) KN	32.6	28.17	43.02
Limit speed (n) r/min	5600	5600	4300
quality (W) kg	4.100	1.950	2.910
Applicable models	Guangzhou Auto Hino (FAST)	FAW Daowe	HINO



315082001	70CL5782F0A	70CL5791F0	70CL5795F0
Φ	Φ57	Φ57	Φ57
	82	91	95
	105.5	114.25	119
	77.9	77.95	77.9
	Φ70	Φ70	Φ70
	28.17	28.17	28.17
	5600	5600	5600
	2.050	2.050	2.250
	FAW Little Aowei	Jinan Haowo	Shangqi



86CL5886F0A	86CL58100F0	77CL58108F0	86CL6079F0
Φ58.2	Φ58.2	Φ57.5	Φ60.2
85.5	100	107.5	79
108	115	123	100.5
134	134	123.8	127.9
Φ85.6	Φ86	Φ77	Φ85.6
43.02	31.90	31.90	31.90
4300	4300	4300	4300
3.925	2.850	2.980	2.740
Shen wo	Volvo	Volvo, Ford, Volkswagen	bus



86CL6082F0B	86CL6082F0C	86CL6084F2/A	86CL6089F0A
Φ60.2	Φ60.2	Φ60	Φ60.2
82	82	84.1	89
103.5	103.5	108.1	112
127.9	127.9	78	77.9
Φ85.6	Φ85.6	Φ85.5	Φ85.6
43.02	31.9	24.5	43.02
4300	4300	5600	4300
3.250	3.250	3.300	2.949
Dongfeng, Beibei, Hongyan Qingqi and Xuzhong Engineering Vehicles	Dongfeng, Beiben, Sax To accomplish great things, do small things first.	Guang Auto Hino (ZF)	FAW Jiefang, Taian Special Vehicle

For those who are eager for success: procrastination and escape are the most devastating and dangerous habits.

To accomplish great things, do small things first.



Bearing code	86CL6089F0B	86CL6089F0C	86CL6090F0
Unit inner diameter (do) mm	Φ60.2	Φ60.2	Φ60.2
Unit fit width (to) mm	89	89	90
Unit width (t1) mm	114.5	112	112
Inlay width with separation fork (H) mm	77.95	77.9	77.9
Contact circle diameter (D1) mm	Φ85.6	Φ85.6	Φ85.6
Dynamic load rating (Ca) KN	43.02	43.02	43.02
Limit speed (n) r/min	4300	4300	4300
quality (W) kg	3.500	2.949	2.900
Applicable models	FAW Liberation	FAW, Qingqi, Sany Heavy Industry, C&T Liuqi, Jirui, Yutong, Auman, Beiben, Jianghuai	Yutong, Xiamen Jinlong Shaanxi Auto North Vehicle



Bearing code	86CL61121F0/A	86CL6390F0	86CL6392F0
Unit inner diameter (do) mm	Φ60.5	Φ62.9	Φ62.9
Unit fit width (to) mm	121	89.5	92
Unit width (t1) mm	143.5	115.5	118.5
Inlay width with separation fork (H) mm	82.5	85.75	85.75
Contact circle diameter (D1) mm	Φ86	Φ85.6	Φ85.6
Dynamic load rating (Ca) KN	31.9	43.02	43.02
Limit speed (n) r/min	4300	4300	4300
quality (W) kg	3.100	2.750	2.880
Applicable models	Saxophone, Benz, Scania	North Ben	Luoyang Yituo



Bearing code	86CL6395F0K	86CL6672F0	86CL6685F0
Unit inner diameter (do) mm	Φ62.9	Φ66.2	Φ66.2
Unit fit width (to) mm	95	72	85
Unit width (t1) mm	121.5	86.5	99
Inlay width with separation fork (H) mm	85.75	134	134
Contact circle diameter (D1) mm	Φ85.6	Φ86	Φ86
Dynamic load rating (Ca) KN	32.60	31.9	31.9
Limit speed (n) r/min	4300	4300	4300
quality (W) kg	3.100	2.284	2.600
Applicable models	Foton Auman	Volvo	Volvo

No dream is more terrible than poverty.



86NL6092F0	86CL60100F0/A	86CL6184F0	87CL61113F2
Φ60.4	Φ60.4	Φ60.5	Φ61
91.5	100.3	84	113.3
107	121.8	106.5	127.1
112	123.9	82.5	138
Φ86	Φ85.6	86	Φ87
43.02	43.02	31.9	32.60
4300	4300	4300	4300
2.967	3.400	2.923	3.610
Saxophone, Scania	Tata Daewoo	Saxophone, Benz, Scandinavia	Isuzu



86CL6395F0A	86CL6395F0C	86CL6395F0G	86CL6395F0J
Φ62.9	Φ62.9	Φ62.9	Φ63.18
95	95	95	94.8
120.5	121.5	121	117.3
85.75	85.75	85.75	85.65
Φ85.6	Φ85.6	Φ85.6	Φ85.6
43.02	43.02	43.02	31.9
4300	4300	4300	4300
2.900	2.950	2.840	3.212
Howard, Volvo, Jinan Heavy Truck	Shaanxi Automobile, Hualing, Jianghuai, Beiben Futian, Liuzhou Balong, Jinan Heavy Duty Truck	North Ben	Nanjing Xugong



86CL66109F0	86NL6773F0	86NL6786F0	3151000493
Φ66.2	Φ67	Φ67	Φ62.5
109	72.5	85.5	95
123	88.5	99.5	115
134	134	134	85.5
Φ86	Φ86	Φ86	Φ85.6
31.9	43.02	43.02	43.02
4300	4300	4300	4300
3.108	2.590	3.200	3.212
Volvo	Volvo	Volvo	SACHS

Perseverance, thinking and thinking.



Bearing code	3151000335	Fukuda	653L-0020A5
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	3151228101	WG9725160510	S31230-01200
Unit inner diameter (do) mm			
Unit fit width (to) mm			
Unit width (t1) mm			
Inlay width with separation fork (H) mm			
Contact circle diameter (D1) mm			
Dynamic load rating (Ca) KN			
Limit speed (n) r/min			
quality (W) kg			
Applicable models			



Bearing code	CT4868F2	CT4867F0	62NT4445F2
Unit inner diameter (do) mm	Φ48	Φ48	Φ44
Unit fit width (to) mm	68	67	45
Unit width (t1) mm	85	76	52.5
Inlay width with separation fork (H) mm	86	75	52.5
Contact circle diameter (D1) mm	/	/	/
Dynamic load rating (Ca) KN	/	/	/
Limit speed (n) r/min	/	/	/
quality (W) kg	/	/	/
Applicable models	bus	Omak3,6	



CT4842F3A	CT708	996714	1014652
Φ48	Φ59	Φ57	Φ59
42	55	40	60
60	62	59	67.5
75	77	74.9	77.5
crew cut		100crew cut	108crew cut
/		/	/
/		/	/
/		/	/
		Bus, truck	/



0002507415	CT4855F3-112 (505202112)	1055302052	CT4445F2
Φ54	Φ47.5	Φ47.5	Φ44
71.2	55	52	45
83.2	71.5	68.5	61
92	74.5	74.5	86
100Bus, truck	92Bus, truck	92Bus, truck	78Bus, truck
/	/	/	/
/	/	/	/
/	/	/	/
Benz	Ankai and other buses	Ankai and other buses	Domestic bus, city bus



CT4847F3-111 (505202111)	CT4853F2	CT4859F2	CT5737F0
Φ47.5	Φ47.5	Φ48	Φ57
47	53	59	37
65.5	69	80	60
74.5	86	86	75
92crew cut	92crew cut		
/	/		
/	/		
/	/		
Ankai and other buses	FAW Light Vehicle		

Performance improvement, pursuit of excellence, challenge yourself, go all out.

Be a man first, then do things.



Bearing code	CT5747F3 (1096302076)	CT5747F3C	CT5752F3
Unit inner diameter (do) mm	Φ57	Φ57	Φ57
Unit fit width (to) mm	47	47	52
Unit width (t1) mm	57	62	62
Inlay width with separation fork (H) mm	85.5	74.9	74.3
Contact circle diameter (D1) mm	100crew cut	100crew cut	100crew cut
Dynamic load rating (Ca) KN	/	/	/
Limit speed (n) r/min	/	/	/
quality (W) kg	/	/	/
Applicable models	Jinlong Yutong	Jinlong Yutong	Jinlong Yutong



Bearing code	CT5755F3 (1096302168)	S31230-6WF1
Unit inner diameter (do) mm	Φ57	Φ61
Unit fit width (to) mm	55	113.3
Unit width (t1) mm	65	127.1
Inlay width with separation fork (H) mm	74.9	138
Contact circle diameter (D1) mm	100crew cut	Φ87
Dynamic load rating (Ca) KN	/	32.60
Limit speed (n) r/min	/	4300
quality (W) kg	/	3.610
Applicable models	Jinlong Yutong	Isuzu



Bearing code	44CL3642F0Accessories	70CL5782F0Accessories	87CL61113F2Accessories
Small inner diameter of separating pulling ring mm	Φ47	Φ73	Φ90.5
Large Internal Diameter of Separating Pull Ring mm	Φ53	Φ79	/
Contact Circle Diameter of Separating Ring mm	Φ70	Φ96	Φ100
Separating pull ring at clamp contact angle	30°	39°	90°
Applicable models	Iveco	FAW	Isuzu



A7MAccessories	86NL6786F0Accessories	86CL70106F0Accessories	86CL5874F0Accessories
Φ89	Φ90.8	Φ90	Φ90.1
Φ96	/	/	/
Φ120	Φ98	Φ102	Φ120
40°	30°	30°	30°
FAW	Volvo	Volvo	Volvo



77CL58108F0 Accessories	86CL6081F2 Accessories	86CL6395F0 Accessories	86CL6395F0A Accessories
Φ80.3	Φ89.3	Φ89	Φ89
Φ83.6	Φ97.2	Φ96	Φ98
Φ94	Φ120	Φ120	Φ120
45°	36°	36°	30°
Volvo	Guang Auto Hino	FAW, Second Automobile, Futian, Shaanxi Automobile	Volvo

Bei Ben, Jinan Heavy Duty Truck, Saxophone



86CL6672F0 Accessories	L4315 Accessories	86CLB20241F2Accessories
Φ90.1	Φ91	Φ91
/	Φ91.5	Φ91.5
Φ120	Φ120	Φ120
30°	34°	34°
Volvo	Scania	Scania



Diligence and steadfastness, honesty and trustworthiness.

Creativity is money, planning shows performance, thinking makes you rich.

OE Control Table for Separating Bearings

No.	OE ref.	NRZ ref.	Automotive type
1	3151 171 001	NT3630F6	STEYR
	3151 011 001		
2	3151 106 041	NT6650F2	VOLVO
3	31230-97502	60RCT3525F0	ISUZU
	8-97316591-0		
4	8-97255313-0	70CT4832F0	ISUZU
5	81TKL4801	70CT4845F0	ISUZU
	1-31310012-0		
6	3151 000 396	86CT5153F0	MB
7	3151 000 397	86CT5164F0	MB
8	3151 152 102	86CT5738F6	BOVA、DAF、SCANIA
	3151 152 102		
	3151 000 395		
9	3151 221 001	86CT5746F0	MERCEDES
	3151 000 419		
10	3151 253 031	86NL5870F0	VOLVO
11	3151 232 101	86CL5874F0	VOLVO
	3151 232 331		
	3151 278 531		
	3151 000 218		
	3151 000 556		
12	3151 000 422	86CL58100F0	VOLVO
13	9112 005 099	77NL58108F0	380clutch (VOLVO、FORD、VW)
14	3151 000 421	77CL58108F0	380clutch (VOLVO、FORD、VW)
15	3151 195 031	86CL6082F0B	DAF、NEOPLAN
	3151 195 033		
	3151 273 531		
	3151 000 157		
16	VALEO 318275	86CL6086F0	VOLVO
17	3151 273 431	86CL6089F0C	DAF
	3151 169 332		
	3151 000 034		
18	3151 228 101	86NL6092F0	SCANIA
	3151 000 272		
	VALEO 079806		

I am confident, I am outstanding: I am fighting, I am successful!

OE Control Table for Separating Bearings

No.	OE ref.	NRZ ref.	Automotive type
19	3151 274 101	86CL6093F0	RENAULT
	3151 274 131		
20	3151 000 156 3100 000 003	86CL6184F0	MB
21	3151 259 031	86CL61121F0	MERCEDES、SCANIA
	3151 000 155		
	3100 002 255		
22	3151 225 001	86CL6395F0C	IVECO、MAN、PEGASO
	3151 203 031		
	3151 225 031		
	3151 000 144		
	3151 169 031		
	3151 169 131		
23	3151 167 432	86CL6672F0	VOLVO
	3151 276 931		
	3151 000 154		
	3100 026 431		
24	3151 276 031	86CL6685F0	VOLVO
	3151 000 163		
	3100 026 433		
	3100 026 434		
	3100 002 459		
25	3151 270 032	86CL66109F0	VOLVO
	3151 277 531		
	3151 000 217		
	3100 002 464		
	3100 026 531		
26	3100 002 247	86NL6773F0	VOLVO
	3100 026 432		
	3151 000 154		
27	3151 002 220	86NL6786F0	VOLVO
28	3100 008 106 VALEO 079974	86CL70106F0	VOLVO
29	3182 009 938	82CLB20241F2	SCANIA

The challenge is opportunity, and breakthrough is growth.

Acronym	Applicable models	Main Sales Specification	Bushing specification	Configuration bearing	Packaging (set)	
B	Beijing BJ1028 small card	φ 25x128	25x30x30	198905	12	
	BeijingBJ-130	φ 25x148	25x30x37	198905	12	
	BeijingBJ-1041	φ 30x148	30x34x35	98206	12	
	north benz	φ 50/51x223	50/51x58x52	329210	4	
C	Dragon King	φ 47x230	47x52x64/55	198909K	4	
D	DongfengEQ-1060	φ 30x178	30x34x40	98206	8	
	DongfengEQ-1061	φ 32x185	32x35x42	198906K	8	
	DongfengEQ-1070	φ 35x192	35x39x43	98907	6	
	DongfengEQ-1071	φ 38x215	38x41x48	129908	6	
	DongfengEQ-140	φ 38x208	38x41x48	129908	6	
	DongfengEQ-144	φ 42x228	42x46x55	329909K	6	
	DongfengEQ-145	φ 38x228	38x41x64/51	429908(409908K)	6	
	DongfengEQ-153	φ 47x240	47x52x64/55	198909K	4	
	Dajinlong	φ 52x248	52x57x65/58	517/52ZSV/YA	4	
	Dongfeng Hercules	φ 52x248	52x57x65/58	517/52ZSV/YA	6	
	Dongfeng Jinba	φ 30x155	30x34x35	98206	12	
	F	Fukuda era598	φ 35x192	35x39x48/43	98907	6
		Fukuda 599	φ 38x208	38x43x48	129908	6
H	Panther.375	φ 25x125	25x28x28	198905	12	
	Hang gua gem1060	φ 30x189	30x34x44	98206	8	
	Hang gua gem1070	φ 32x180	32x36x42	817/32ZS/YA	8	
	Haowo09	φ 45x200	45x54x35	917/45ZS/YA	6	
	Yellow Sea Passenger Car	φ 47x216	47x56x38/34	198909K	4	
	Valin	φ 50x253	HMK5030Needle roller sleeve50x62x30	329210	4	
			HMK5045Needle roller sleeve50x62x45			
	HF-6730	φ 35x192	35x39x48/43	98907	6	
J	Jianghuai6700	φ 30x188	30x34x50	409906K	8	
	Hongyan King Kong	φ 50x230	50x55x56.5	329210	4	
	golden dragon6892	φ 42x228	42x46x55	329909	6	
	golden dragon6796	φ 38x228	38x41x64/21	429908	6	
	golden dragon6820	φ 42x238	42x46x65/55	329908K	6	
	golden dragon6790	φ 35x192	35x39x48/43	98907	6	
	golden dragon6890	φ 38x215	38x41x51	129908	6	
	golden dragon6791	φ 38x215	38x42x51	129908	6	
	golden dragon6885	φ 42x238	42x46x66/55	329908K	6	
	golden dragon6112	φ 47x240	47x52x64/55	198909K	4	
	golden dragon6110、6113	φ 47x240	47x52x64/55	198909K	4	
	Jianghuai6800	φ 32x185	32x36x40	817/32ZS/YA	8	
	Jianghuai 6800 Extended Type	φ 32x197	32x36x40	817/32ZS/YA	8	
	Jianghuai6782、6853	φ 40x228	40x46x58	51708ZSV/YA	6	
	Jianghuai Geerfa	φ 50x244	50x56x65/54	51710ZSV/YA	4	
	J	liberationCA-1046L	φ 25x148	25x28x34	198905	12
		liberationCA-1047L	φ 25x148	25x30x37	198905	12

Vehicle steering section main pin repair package models, specifications and related configuration dimensions

Acrony	Applicable models	Main Sales Specification	Bushing specification	Configuration	Packaging (sets)
J	Liberation of three tons of king	φ 35x192	35x39x48/43	98907	6
	liberationCA-141	φ 38x220	38x41x51	129908	6
	liberationCA-151	φ 42x230	42x45x59	329909	6
	Liberation of Jiuping Chai	φ 45x245	45x49x65	329909A	4
	liberationCA-16T	φ 48x278	48x53x76	329909A	4
	liberationJ6	φ 50x250	50x55x65/55	329210	4
	Jiangsu Yingtian	φ 34x180	34x38x40	517/34ZSV/YA	8
K	Kangling II	φ 30x148	30x34x35	98206	8
N	NanjingNJ-131	φ 30x178	30x33x38	98206	8
	NanjingNJ-1053、1063	φ 35x195	35x39x43	98907	6
O	Oman1026	φ 35x190	35x39x48/42	98907	6
	Oman (Qingdao Chassis)	φ 45x240	45x49x65/60	329909A	4
	Oman 260	φ 45x245	45x49x65	329909A	4
	Oman Master	φ 52x248	52x57x65/58	517/52ZSV/YA	4
S	Times light truck	φ 30x165	30x34x44	98206	10
	Times Light Truck Enhanced Type	φ 30x165	30x35x44	98206	10
	Times King Kong (Zibo Qingqi)	φ 30x150	30x34x35	98206	12
	Time Ruiwo240	φ 38x235	38x42x65/50	429908	6
	Time Ruiwo160	φ 42x208	42x46x47	329909	6
	Time Ruiwo210	φ 52x248	52x57x65/58	517/52ZSV/YA	4
	Steyr	φ 43/45/47x205	43/45/47 x 52/54/56 x 38/58/35	329910	4
	Prince Steyr King (Improved)	φ 50x230	50x55x56.5	329210	4
	Shaanxi Auto delong	φ 49.5/50x224	49.5x58x52	329910	4
			HMK505825Needle bearing50x58x25		
	Shaanxi Auto delong (new)	φ 49.5/50.4x224	49.5x58x52	329910	4
			HMK505825Needle bearing50x58x25		
	Shaanxi Auto delong3000	φ 54x236	54x62x50	517/54ZSV/YA	4
			HMK5427Needle bearing54x62x27		
	Shaanxi Auto Aolong	φ 43/45/47x206	43/45/47x52/54/56x38/58/35	329910	4
W	IsuzuNHR	φ 25x168	25x29x40	409905K	12
X	New Blue Arrow	φ 30x158	30x34x35	98206	10
	Thirteen tons of Xiangqiao	φ 52x248	52x57x65/58	517/52ZSV/YA	4
	Xiao JinlongCA-5063	φ 38x215	38x41x64/51	129908	6
	The Second Generation of Xinkangling	φ 30x148	30x34x35	98206	12
Y	FAW Jinka King	φ 30x125	30x34x35	98206	12
	FAW Red Tower	φ 30x158	30x34x35	98206	10
	FAW Welding	φ 48x242	48x53x65	329910A	4
	FAW Welding (new)	φ 48x242	48x53x65	329910A	4
	Yangzhou Yaxing 663	φ 42x238	42x46x65/55	329908K	4
	King of Coal Transport (EQ-1094)	φ 42x240	42x46x64/50	329908K	4
	Yuejin Light Card-311	φ 30x184	30x34x50	409906K	10
Z	violet	φ 52x247	52x57x65/58	517/52ZSV/YA	4

Use your hands to forge ahead and use your abilities to create the future.